

	产品型号 Model Number	WL-433E50
	频率 Frequency Range (MHz)	433
	增益 Gain (dBi)	2
	极化方式 Polarization Type	Vertical
	驻波比 V.S.W.R. (s)	2
	阻抗 Input Impedance (Ω)	50
	接口型号 Connector Type	SMA Male or Customized
产品尺寸 Dimensions (mm)	50	

	产品型号 Model Number	WL-433E67-100
	频率 Frequency Range (MHz)	433
	增益 Gain (dBi)	2
	极化方式 Polarization Type	Vertical
	驻波比 V.S.W.R. (s)	2
	阻抗 Input Impedance (Ω)	50
	接口型号 Connector Type	U.FL/ IPEX or Customized
产品尺寸 Dimensions (mm)	67	

	产品型号 Model Number	WL-433E108
	频率 Frequency Range (MHz)	433
	增益 Gain (dBi)	2
	极化方式 Polarization Type	Vertical
	驻波比 V.S.W.R. (s)	2
	阻抗 Input Impedance (Ω)	50
	接口型号 Connector Type	SMA Male or Customized
产品尺寸 Dimensions (mm)	108	

	产品型号 Model Number	WL-433E170
	频率 Frequency Range (MHz)	433
	增益 Gain (dBi)	2
	极化方式 Polarization Type	Vertical
	驻波比 V.S.W.R. (s)	2
	阻抗 Input Impedance (Ω)	50
	接口型号 Connector Type	TNC Male or Customized
产品尺寸 Dimensions (mm)	170	

	产品型号 Model Number	WL-433E105-3000
	频率 Frequency Range (MHz)	174-230/470-862
	增益 Gain (dBi)	12
	极化方式 Polarization Type	Vertical
	驻波比 V.S.W.R. (s)	2
	阻抗 Input Impedance (Ω)	50
	接口型号 Connector Type	F Male or Customized
产品尺寸 Dimensions (mm)	62*105	

	产品型号 Model Number	WL-433E140-3000
	频率 Frequency Range (MHz)	433
	增益 Gain (dBi)	2
	极化方式 Polarization Type	Vertical
	驻波比 V.S.W.R. (s)	2
	阻抗 Input Impedance (Ω)	50
	接口型号 Connector Type	SMA Male or Customized
产品尺寸 Dimensions (mm)	29*140	

	产品型号 Model Number	WL-433E150-3000
	频率 Frequency Range (MHz)	174-230/470-862
	增益 Gain (dBi)	3
	极化方式 Polarization Type	Vertical
	驻波比 V.S.W.R. (s)	2
	阻抗 Input Impedance (Ω)	50
	接口型号 Connector Type	F Male or Customized
产品尺寸 Dimensions (mm)	29*150	

	产品型号 Model Number	WL-433E168-3000
	频率 Frequency Range (MHz)	433
	增益 Gain (dBi)	3
	极化方式 Polarization Type	Vertical
	驻波比 V.S.W.R. (s)	2
	阻抗 Input Impedance (Ω)	50
	接口型号 Connector Type	SMA Male or Customized
产品尺寸 Dimensions (mm)	29*168	

	产品型号 Model Number	WL-433E170-3000
	频率 Frequency Range (MHz)	174-230/470-862
	增益 Gain (dBi)	36
	极化方式 Polarization Type	Vertical
	驻波比 V.S.W.R. (s)	2
	阻抗 Input Impedance (Ω)	50
	接口型号 Connector Type	F Male or Customized
产品尺寸 Dimensions (mm)	72*170	

	产品型号 Model Number	WL-433E208-3000
	频率 Frequency Range (MHz)	433
	增益 Gain (dBi)	30
	极化方式 Polarization Type	Vertical
	驻波比 V.S.W.R. (s)	2
	阻抗 Input Impedance (Ω)	50
	接口型号 Connector Type	SMA Male or Customized
产品尺寸 Dimensions (mm)	62*208	

	产品型号 Model Number	WL-433E9518-3000
	频率 Frequency Range (MHz)	433
	增益 Gain (dBi)	2
	极化方式 Polarization Type	Vertical
	驻波比 V.S.W.R. (s)	2
	阻抗 Input Impedance (Ω)	50
	接口型号 Connector Type	SMA Male or Customized
产品尺寸 Dimensions (mm)	95*18	

	产品型号 Model Number	WL-433E1522-3000
	频率 Frequency Range (MHz)	433
	增益 Gain (dBi)	2
	极化方式 Polarization Type	Vertical
	驻波比 V.S.W.R. (s)	2
	阻抗 Input Impedance (Ω)	50
	接口型号 Connector Type	SMA Male or Customized
产品尺寸 Dimensions (mm)	315*22	

	产品型号 Model Number	WL-433E43-1
	频率 Frequency Range (MHz)	433
	增益 Gain (dBi)	1.5
	极化方式 Polarization Type	Vertical
	驻波比 V.S.W.R. (s)	2
	阻抗 Input Impedance (Ω)	90
	接口型号 Connector Type	Gold-plated copper
产品尺寸 Dimensions (mm)	43	

	产品型号 Model Number	WL-433E2717-100
	频率 Frequency Range (MHz)	433
	增益 Gain (dBi)	1.5
	极化方式 Polarization Type	Vertical
	驻波比 V.S.W.R. (s)	2
	阻抗 Input Impedance (Ω)	50
	接口型号 Connector Type	U.FL/ IPEX or Customized
产品尺寸/长度 Dimensions(mm)/Texture	27*17/FPC	

	产品型号 Model Number	WL-433E9407-100
	频率 Frequency Range (MHz)	433
	增益 Gain (dBi)	1.5
	极化方式 Polarization Type	Vertical
	驻波比 V.S.W.R. (s)	2
	阻抗 Input Impedance (Ω)	50
	接口型号 Connector Type	U.FL/ IPEX or Customized
产品尺寸/长度 Dimensions(mm)/Texture	40*7/PCB	

	产品型号 Model Number	WL-433E9617-100
	频率 Frequency Range (MHz)	433
	增益 Gain (dBi)	2
	极化方式 Polarization Type	Vertical
	驻波比 V.S.W.R. (s)	2
	阻抗 Input Impedance (Ω)	50
	接口型号 Connector Type	U.FL/ IPEX or Customized
产品尺寸/长度 Dimensions(mm)/Texture	61*7/PCB	